

PTV-3200

32" All-in-One LCD TV Display



Features

- 32" WXGA(1366 x 768) resolution, 16:9 signage display.
- High panel brightness and contrast- 1,000:1 contrast ratio.
- Fast response time – 8 ms grey to grey.
- Wide viewing angle – 176 degree.
- Configurable ambient light sensor.
- OSD controls the black level of VGA for a perfect balanced images.
- Extensive control and diagnostic functions through RS-232
- RS-232 loop-through function allows controlled from a single location.
- Displaying two images – Picture in Picture, Picture and Picture.
- 50,000 Hours panel life offered
- Low noise, fanless cooling system.
- VESA mounting structure for easy installation.
- Audio pre-amp input mode.

Specification:

LCD PANEL:	Brightness	550 cd/m2 (typical)
	Contrast Ratio	1000:1
	Viewing Angle	H:176 degree / V: 176 degree
	Response Time	8 ms(GTG)
	Supported colors	16.7M colors
	Resolution	1366 x 768
DISPLAY:	Horizontal Frequency	30K ~ 90KHz
	Vertical Frequency	50 ~ 75KHz
	Input Resolution	1360 x 768 @75Hz (Analog) 1920 x 1080 @60Hz(Digital)
	DDC	DDC 2B
	OSD Control	RS-232,Push button,IR Remote controller
	OSD Language	English
COMPUTER:	CPU	Intel C-M 1.0GHz
	Chipset	Intel 852GME + ICH4
	Memory	256MB
	HDD	2.5" 40GB
	Watchdog Timer	1~255 sec
	USB	2 x USB2.0
	LAN	1 x 10/100 Mbps
	Expansion	1 x PCMCIA type II/III
	Operation System	Windows2000/XP/XPe
FEATURES:	Video Signal Type	RGB Analog /Digital
	Connector	15 pin D-Sub/ DVI / Component / S-video /AV/RJ-45/PS2/USB/PCMCIA
	Power Supply	AC 100~240V
	Dimension w/o Stand	942mm(W) x 484mm(H) x 121mm(D)
	Diagonal	32.02"
	Weight	23 kg
	Wall/Arm Mount Type	100mmx100mm,200mmx200mm VESA
	I/O Cover	Yes
	Multimedia	PIP, RAP, Zoom
	AV / TV	W/O TV Tuner
	Audio	2x 8W
	Fanless Design	Yes
	Stand	Optional
Environmental:	Operating Temperature	5°C ~ 40°C
	Operating Humidity	20~80%
	Storage Temperature	-20°C ~60°C
	Storage Humidity	10~90%
COMPLIANCE:		CE,FCC,VCCI,BSMI,CCC,CB,UL/cUL,T UV/PS, RoHS/WEEE

Dimensions:

